



IPU10

The IPU10 vertical lifting clamp is used for lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed. The hinged hoisting eye allows for the clamp to place and lift the load from any direction, or with a multiple leg sling without side-loading the clamp.

Universal - for lifting in any direction

- Available in capacities of .5 thru 30 metric tons (Higher Working Load Limits are available upon request).
- Wide variety of jaw openings available: 0° to 6.1”.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Company name (CrosbyIP), logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Available in a variety of styles:
 - IP10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
 - IP10J - Larger jaw opening.
 - IP10S - For use with Stainless Steel material.
 - IP10H - For use with materials with a surface hardness to 472HV10 (450 HB).
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- Optional IP-5000 Stinger assembly available (see page 428). Allows for easy connection between the clamp and hoist hook.
- Minimum WLL of 10% of maximum WLL.
- For use with materials with a surface hardness to 279HV10. Only 5% minimum WLL is needed.
- Maintenance and repair kits are available.
- Manufactured by an ISO 9001 facility.
- All sizes are **RFID EQUIPPED**.



IPU10S

IPU10S: For use with Stainless Steel material.
IPU10H: For use with materials with a surface hardness to 47Rc (450 HB).



Load Rated

Model IPU10 / IPU10J / IPU10S / IPU10H

Model	Working Load Limit (t)*	IPU10 Stock No.	Weight Each (lbs.)	Dimensions (in.)									
				Jaw A	B	C	D	E	F	G	H	J	K
IPU10	0.25	2703850	4.19	0 - 0.63	1.73	5.12	8.50	1.57	4.53	1.65	1.10	-	0.43
IPU10	0.5	2701675	4.19	0 - 0.63	1.73	5.12	8.50	1.57	4.53	1.65	1.10	-	0.43
IPU10	1	2701663	5.29	0 - 0.75	1.77	5.47	8.86	1.57	5.00	1.65	1.50	-	0.43
IPU10	2	2701677	18.3	0 - 1.38	3.07	7.91	14.49	2.76	7.40	2.52	2.17	-	0.63
IPU10	3	2701665	32.6	0 - 1.56	3.94	9.96	17.17	2.95	8.74	3.07	2.36	-	0.79
IPU10	4.5	2701667	35.3	0 - 1.56	3.94	9.96	17.17	2.95	8.94	3.23	2.56	-	0.79
IPU10	6	2701669	52.9	0 - 2.00	4.96	11.89	20.67	3.15	11.50	3.31	3.74	1.73	0.79
IPU10	9	2701671	65.0	0 - 2.00	4.96	12.80	21.73	3.15	12.20	3.70	4.09	1.73	0.79
IPU10	12	2701679	126	0 - 2.13	6.30	15.43	24.25	3.15	17.05	4.76	5.39	1.61	0.98
IPU10	16	2701683	174	0.2 - 2.50	7.09	18.23	28.98	3.46	19.37	4.76	6.02	1.77	0.98
IPU10	22.5	2701687	278	0.2 - 3.13	8.74	21.81	33.98	4.33	22.24	5.47	7.32	1.93	0.98
IPU10	30	2701691	311	0.2 - 3.13	8.74	21.81	34.17	4.33	22.83	6.02	7.32	2.13	1.18
IPU10J	3	2702465	38.1	1.57 - 3.15	4.53	10.63	17.01	2.95	10.91	3.07	2.64	-	0.79
IPU10J	6	2702469	58.4	2.00 - 4.00	4.96	11.89	20.28	3.15	13.23	3.31	3.74	1.73	0.79
IPU10J	9	2701673	67.2	2.00 - 4.00	4.96	12.80	21.65	3.15	14.17	3.70	4.13	1.73	0.79
IPU10J	12	2701681	143	2.13 - 4.25	7.01	17.24	26.06	3.15	19.33	4.76	5.35	1.61	0.98
IPU10J	16	2701685	187	2.50 - 5.00	8.19	20.51	30.87	3.46	22.13	4.76	6.30	1.77	0.98
IPU10J	22.5	2701689	328	3.13 - 6.13	10.04	24.72	36.93	4.33	25.98	5.47	7.72	1.93	0.98
IPU10J	30	2701693	364	3.13 - 6.13	10.04	24.72	37.09	4.33	25.98	6.02	7.72	2.13	1.18
For stainless steel - with universal hoisting eye													
IPU10S	0.5	2702275	4.19	0 - 0.63	1.73	5.12	8.50	1.57	4.53	1.65	1.10	-	0.43
IPU10S	1	2702263	5.29	0 - 0.75	1.77	5.47	8.86	1.57	5.00	1.61	1.50	-	0.43
IPU10S	2	2702277	18.7	0 - 1.38	3.07	7.91	14.49	2.76	7.40	2.52	2.17	-	0.63
IPU10S	3	2702265	32.6	0 - 1.56	3.94	9.96	17.17	2.95	8.74	3.07	2.36	-	0.79
IPU10S	4.5	2702267	35.3	0 - 1.56	3.94	9.96	17.17	2.95	8.94	3.23	2.56	-	0.79
IPU10S	6	2702269	52.9	0 - 2.00	4.96	11.89	20.67	3.15	11.50	3.31	3.74	1.73	0.79
IPU10S	9	2702271	65.0	0 - 2.00	4.96	12.80	21.73	3.15	12.20	3.70	4.09	1.73	0.79
IPU10S	12	2702279	126	0 - 2.13	6.30	15.43	24.25	3.15	17.05	4.76	5.39	1.61	0.98
For very hard materials - with universal hoisting eye													
IPU10H	0.5	2702175	4.19	0 - 0.63	1.73	5.12	8.50	1.57	4.53	1.65	1.10	-	0.43
IPU10H	0.75	2702163	5.29	0 - 0.79	1.77	5.47	8.86	1.57	5.00	1.61	1.50	-	0.43
IPU10H	1	2702177	18.3	0 - 1.38	3.07	7.91	14.49	2.76	7.40	2.52	2.17	-	0.63
IPU10H	2	2702165	32.6	0 - 1.56	3.94	9.96	17.17	2.95	8.74	3.07	2.36	-	0.79
IPU10H	3	2702167	35.3	0 - 1.56	3.94	9.96	17.17	2.95	8.94	3.23	2.56	-	0.79
IPU10H	4.5	2702169	52.9	0 - 2.00	4.96	11.89	20.67	3.15	11.50	3.31	3.74	1.73	0.79
IPU10H	6	2702171	65.0	0 - 2.00	4.96	12.80	21.73	2.76	12.20	3.70	4.09	1.73	0.79

* Design Factor based on EN 13155 and ASME B30.20. Model IPU10R (remote control opening and closing via a cable) on request. Model IPU10W (wedge) available on request.

