





LEVER CHAIN HOIST X5-SERIES



FEATURES

- Brake sets and operates without minimum preload
- 100% inspection of hooks per ASME B30 and easy hook replacement is permitted by bolted hook blocks
- All steel body for durable strength in a smaller size
- Powder coat and plated external I parts to resist corrosion
- Laser etched stainless steel nameplates with required OSHA /ASME B30 warnings, model and stamped serial number
- Long life fused brake friction disc cannot crack, shatter or absorb moisture
- Grade 100 zinc plated load chain made in Japan or EU
- Optional overload protection is by one directional slip clutch that only slips in the lift direction
- Ambient Temperature range: -40° to +140°F (-40° to +60°C)
- Meets: OSHA, ASME B30.21 and ASME HST-3. In addition the ultimate strength is 5 times Work Load Limit (WLL) meeting structural requirements of ASME HST-3 Appendix A, for use in marine and other applications as specified by US Department of Defense DOD.
 APEX rating: ATEX certified II 3GD c IIB 60°C X for limited use in Hazardous Environments
 - Final assembly and load test in the USA from imported components. Supplied with certificate by serial
 - Open chain guard allows visual inspection and does not trap contamination



STOCK NO.	UPC NO.	DESCRIPTION	WLL (US T.)	PART	WEIGHT (LBS.)	DIMENSIONS (IN.)							
						A Min.	A1	с	D	E W/LATCH		P (lbs)	W (lbs) /FT.Lift
RATPUL11/8X5L5-25A	X5L02250-05	LEVER CHAIN HOIST X5 5' 1020 KG- 1-1/8 TON US	1-1/8	1	14.0	11.8	3.9	4.7	9.6	0.9	5.9	52	0.5
RATPUL13/4X5L5-25A	X5L03528-05	LEVER CHAIN HOIST X5 5' 1600 KG- 1-3/4 TON US	1-3/4	1	19.5	13.2	4.1	5.0	10.4	1.2	6.6	72	0.7
RATPUL31/2X5L5-25A	X5L07056-05	LEVER CHAIN HOIST X5 5' 3200 KG- 3-1/2 TON US	3-1/2	1	32.0	15.6	4.6	6.3	16.3	1.3	7.9	84	1.5
RATPUL7X5L10-25A	X5L14000-10	LEVER CHAIN HOIST X5 10' 6350 KG- 7 TON US	7	2	57.0	21.3	4.6	8.6	16.3	1.6	7.9	86	3.2





www.lamestpierre.com

Montréal	T 514 354-4219 /	1 800 361-4019
Québec	T 418 652-9759 /	1 800 652-9759
Saguenay	T 418 696-9759 /	1 866 696 9759