

**S.T.P. ROUND SLINGS**

**L** REGULAR SLING

- Available in industry-standard capacities.
- 2' to 120' long
- Double-layer cover
- Polyester fiber
- Polyester outer cover available in industry-standard colors.
- Safety factor 5 : 1

**LXC** MEGA HIGH-CAPACITY SLING

- Available in various capacities from 10,000 lb to 500, 000 lb.
- 2' to 120' long
- Double-layer cover
- Spectra® Fiber
- Blue Nylon outer cover interwoven with protective NANO microfiber
- Safety factor 5 :1

**LXC-DL** DUO HIGH-CAPACITY SLING

- Available in various capacities from 20,000 lb. to 1,000,000 lb.
- 2' to 120' long
- Double-layer cover
- Spectra® Fiber
- Blue Nylon outer cover interwoven with protective NANO microfiber
- Safety factor 5 :1

**LXC-7 :1** ULTIME HIGH-CAPACITY SLING

- Available in various capacities from 10,000 lb. to 500, 000 lb.
- 2' to 120' long
- Double-layer cover
- Spectra® Fiber
- Blue Nylon outer cover interwoven with protective NANO microfiber
- Safety factor 7 :1

**LX** REGULAR PLUS SLING

- Available in various capacities from 3,000 lb to 150,000 lb.
- 2' to 120' long
- Double-layer cover
- Polyester fiber
- Blue nylon outer cover interwoven with protective NANO microfiber
- Safety factor 5 :1

**ROUND SLINGS**  
**S.T.P.**

 **Safety**

 **Task**

 **Precision**

Lengths accurate to almost 99% for slings of the same model and the same lengths. Special wear pads available on request.

EACH SLING COMPLIES WITH ASME B30.9, OSHA REGULATIONS & WSTDA STANDARDS.