



**LAM-É  
ST-PIERRE**



## **POLYESTER WEB SLING 1 INCH, TYPE 3 AND TYPE 4 SIMPLE AND DOUBLE PLY**

The straps have a width ranging from 1 inch to 24 inches. They offer great flexibility to meet all your lifting needs up to 120,000 pounds. Our commercial and industrial straps meet the stringent standards of ASME and WSTDA. Our straps are made of high tenacity synthetic yarns, chosen for their exceptional strength, abrasion resistance and chemical properties

### **FEATURES**

- Lightweight and easy to handle
- Easy to read labels
- All nylon or polyester slings have a safety factor of 5:1
- Use them with overhead cranes, winches or hoists
- The slings can be designed to double, triple or quadruple ply
- Optional wear protection
- *Other lengths available in special manufacturing on request*



STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
	ONE PLY				
419013PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 3' LSP	0.21	0.10
419014PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 4' LSP	0.24	0.11
419016PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 6' LSP	0.28	0.13
419018PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 8' LSP	0.34	0.15
4190110PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 10' LSP	0.39	0.18
4190112PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 12' LSP	0.44	0.20
4190114PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 14' LSP	0.50	0.23
4190116PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 16' LSP	0.55	0.25
4190118PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 18' LSP	0.61	0.28
4190120PLSP-6P	1	25	POLYESTER SLING SPN-4 1901 20' LSP	0.66	0.30

**Safety Factor 5:1**

MODEL	WORKING LOAD LIMITS					
	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 1 PLY, 1 IN.	1,600	1,280	3,200	726	581	1,453

• **Never exceed specified working loads.**  
Capacity of synthetic slings (nylon or polyester) according to class 7.  
In accordance with ASME B30.9

STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
	TWO PLY				
429012PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 2' LSP	0.35	0.16
429013PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 3' LSP	0.50	0.23
429014PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 4' LSP	0.70	0.32
429015PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 5' LSP	0.80	0.36
429016PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 6' LSP	0.90	0.41
429017PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 7' LSP	1.01	0.46
429018PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 8' LSP	1.10	0.50
4290110PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 10' LSP	1.35	0.61
4290112PLSP-6P	1	25	POLYESTER SLING SPN-4 2901 12' LSP	1.60	0.73

**Safety Factor 5:1**

MODEL	WORKING LOAD LIMITS					
	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 2 PLY, 1 IN.	3,100	2,480	6,200	1,407	1,126	2,815

• **Never exceed specified working loads.**  
Capacity of synthetic slings (nylon or polyester) according to class 7.  
In accordance with ASME B30.9



**LAM-É  
ST-PIERRE**

[www.lamestpierre.com](http://www.lamestpierre.com)

Montréal | T 514 354-4219 / 1 800 361-4019  
 Québec | T 418 652-9759 / 1 800 652-9759  
 Saguenay | T 418 696-9759 / 1 866 696 9759