



**LAM-É
ST-PIERRE**



POLYESTER WEB SLING 2 INCH, TYPE 3 AND TYPE 4 SIMPLE AND DOUBLE PLY

The straps have a width ranging from 1 inch to 24 inches. They offer great flexibility to meet all your lifting needs up to 120,000 pounds. Our commercial and industrial straps meet the stringent standards of ASME and WSTDA. Our straps are made of high tenacity synthetic yarns, chosen for their exceptional strength, abrasion resistance and chemical properties

FEATURES

- Lightweight and easy to handle
- Easy to read labels
- All nylon or polyester slings have a safety factor of 5:1
- Use them with overhead cranes, winches or hoists
- The slings can be designed to double, triple or quadruple ply
- Optional wear protection
- *Other lengths available in special manufacturing on request*



STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
419023PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 3' LSP	0.38	0.17
419024PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 4' LSP	0.48	0.22
419026PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 6' LSP	0.60	0.27
419028PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 8' LSP	0.72	0.33
4190210PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 10' LSP	0.82	0.37
4190212PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 12' LSP	0.91	0.42
4190214PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 14' LSP	1.05	0.47
4190216PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 16' LSP	1.17	0.53
4190218PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 18' LSP	1.28	0.58
4190220PLSP-6P	2	51	POLYESTER SLING SPN-4 1902 20' LSP	1.40	0.64

Safety Factor 5:1

MODEL	WORKING LOAD LIMITS					
	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 1 PLY, 2 IN.	3,100	2,480	6,200	1,407	1,126	2,815

• **Never exceed specified working loads.**
Capacity of synthetic slings (nylon or polyester) according to class 7.
In accordance with ASME B30.9

STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
429022PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 2' LSP	0.75	0.34
429023PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 3' LSP	1.05	0.48
429024PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 4' LSP	1.30	0.59
429025PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 5' LSP	1.55	0.70
429026PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 6' LSP	1.80	0.82
429028PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 8' LSP	2.25	1.02
4290210PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 10' LSP	2.75	1.25
4290212PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 12' LSP	3.20	1.45
4290214PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 14' LSP	3.65	1.66
4290216PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 16' LSP	4.20	1.91
4290218PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 18' LSP	4.60	2.09
4290220PLSP-6P	2	51	POLYESTER SLING SPN-4 2902 20' LSP	5.05	2.29

Safety Factor 5:1

MODEL	WORKING LOAD LIMITS					
	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 2 PLY, 2 IN.	6,200	4,960	12,400	2,815	2,252	5,630

• **Never exceed specified working loads.**
Capacity of synthetic slings (nylon or polyester) according to class 7.
In accordance with ASME B30.9



**LAM-É
ST-PIERRE**

www.lamestpierre.com

Montréal | T 514 354-4219 / 1 800 361-4019
Québec | T 418 652-9759 / 1 800 652-9759
Saguenay | T 418 696-9759 / 1 866 696 9759