



**LAM-É  
ST-PIERRE**



## **POLYESTER WEB SLING 4 INCH, TYPE 3 AND TYPE 4 SIMPLE AND DOUBLE PLY**

The straps have a width ranging from 1 inch to 24 inches. They offer great flexibility to meet all your lifting needs up to 120,000 pounds. Our commercial and industrial straps meet the stringent standards of ASME and WSTDA. Our straps are made of high tenacity synthetic yarns, chosen for their exceptional strength, abrasion resistance and chemical properties

### **FEATURES**

- Lightweight and easy to handle
- Easy to read labels
- All nylon or polyester slings have a safety factor of 5:1
- Use them with overhead cranes, winches or hoists
- The slings can be designed to double, triple or quadruple ply
- Optional wear protection
- *Other lengths available in special manufacturing on request*



ONE PLY					
STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
419043PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 3' LSP	0.77	0.35
419044PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 4' LSP	0.87	0.39
419046PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 6' LSP	1.08	0.41
419048PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 8' LSP	1.29	0.59
4190410PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 10' LSP	1.51	0.69
4190412PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 12' LSP	1.72	0.78
4190414PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 14' LSP	1.93	0.88
4190416PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 16' LSP	2.14	0.97
4190418PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 18' LSP	2.35	1.07
4190420PLSP-6P	4	102	POLYESTER SLING SPN-4 1904 20' LSP	2.56	1.16

**Safety Factor 5:1**

WORKING LOAD LIMITS						
MODEL	VERTICAL 90 °	CHOKER 90 °	BASKER 90 °	VERTICAL 90 °	CHOKER 90 °	BASKER 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 1 PLY, 4 IN.	6,200	4,960	12,400	2,815	2,252	5,630

• **Never exceed specified working loads.**  
**Capacity of synthetic slings (nylon or polyester) according to class 7.**  
**In accordance with ASME B30.9**

TWO PLY					
STOCK NO.	WIDTH		DESCRIPTION	APPROX. WEIGHT	
	in	mm		lb	kg
429043PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 3' LSP	2.00	0.91
429044PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 4' LSP	2.55	1.16
429046PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 6' LSP	3.50	1.59
429048PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 8' LSP	4.55	2.06
4290410PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 10' LSP	5.35	2.43
4290412PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 12' LSP	6.30	2.86
4290414PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 14' LSP	7.25	3.29
4290416PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 16' LSP	8.10	3.67
4290420PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 20' LSP	10.00	4.54
4290425PLSP-6P	4	102	POLYESTER SLING SPN-4 2904 25' LSP	12.40	5.63

**Safety Factor 5:1**

WORKING LOAD LIMITS						
MODEL	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °	VERTICAL 90 °	CHOKER 90 °	BASKET 90 °
	lb	lb	lb	kg	kg	kg
SPN4, 2 PLY, 4 IN.	11,000	8,800	22,000	4,990	3,990	9,980

• **Never exceed specified working loads.**  
**Capacity of synthetic slings (nylon or polyester) according to class 7.**  
**In accordance with ASME B30.9**