

DELTA PALAN offers you the R-W-M Electric chain hoist

The W-series range of electric chain hoists can be distinguished by the following; its extremely compact size giving the best possible closed headroom, its exceptional quality and its high level of reliability. All are achieved by having the highest quality manufacturing standards, continuous improvements and quality control. All mechanical parts are examined under stringent conditions and rigorously tested, including long term performance testing to ensure the highest quality, efficiency and extended product durability.

Standard equipment and advantages included

- Chain container
- 2 year warranty on parts and labour
- Spare parts availability
- Overload protection (friction protects from overloading)
- Electromagnetic brakes for quick and precise braking
- Ergonomic pendant with e-stop button and low voltage (24V)
- ✓ Variable speeds available
- Rigid or trolley suspension
- ✓ IP55 protection (dust and humidity proof)
- ▼ Thermal protection
- ✓ Galvanized load chain (10' standard other lengths available upon request)
- ✓ Technical information/assistance available
- CSA Approved



Available in the following capacities and voltages

Série W

- 125 kg (1/8 Metric Tons) available in 120, 240 and 600 volts.
- 250 kg (1/4 Metric Tons) available in 120, 240 and 600 volts.
- 500 kg (1/2 Metric Tons) available in 120, 240 and 600 volts.
- 1000 kg (1 Metric tons) available in 120, 240 and 600 volts.

Série WR

- 2000 kg (2 Metric Tons) available in 600 volts.
- 3000 kg (3 Metric Tons) available in 600 volts.
- 5000 kg (5 Metric Tons) available in 600 volts.

Available options

Radio Control, personalized hoists, mechanical or motorized trolleys













